

resilience
E Series

Revolutionary
in-line salt
chlorinator for
pools

MAGEN
ECO-ENERGY



Resilience E - Natural Salt Chlorinator

Unique Features:

- Simplest installation in the market
- Designed to work with variable speed pumps
- Bi-directional flow sensor
- Double "low flow" protection
- Full range input voltage 110-220 Vac
- Built in salinity and water temperature sensors
- Replaceable electrolysis cartridge

Control Panel Display:

- 24 hours super chlorination mode
- Service and maintenance built in alerts
- 4 button operation
- Cell life low LED indicator
- Clean cell identification and alert



Choosing the Correct Cell Model for Pool Size

Cell Model	E 18		E 40		E 60	
	Ambient Temperature		Ambient Temperature		Ambient Temperature	
	Above 26 °C	Below 26 °C	Above 26 °C	Below 26 °C	Above 26 °C	Below 26 °C
Maximum pool size in cub. mtrs*	50	60	80	120	120	150
Chlorine Output g/h	14		26		36	

* Maximum pool size is subjected to using Cyanuric acid to balance pool water.

* Suitable for private pools!

* In special pools (Overflow pools, Lap pools, , Hydrotherapy pools, Public/Commercial pools) or in cases of heightened chlorine demand (such as warmer climates, high bathers load, etc.), it is recommended to choose a larger model.

Standards & Certifications

ISO 9001:2015	International
ISO 14001:2015	International
IP66	International
UL	U.S.A
CE	Europe

